



X-SCO/N DATA SHEET


Suspended ceiling fastener



X-SCO/N Ceiling fastener


Product info

Product description

Designation	Features
<p>X-SCO/N</p> 	<ul style="list-style-type: none"> • Higher productivity – up to 20 % project time savings frees up time to take on more projects, ultimately increasing your bottom line • More comfortable jobsites – less noise, dust and vibration when compared with drilling, helping to fulfill health and safety requirements on jobsites • Peace of mind – European Technical Assessment (ETA) approved system for suspended ceilings • Easier to install – quickly install a suspended ceiling hanger in seconds with Hilti direct fastening tools • Added convenience as hangers can be fitted before the fastener is driven • One clip suitable for both eyelet and Nonius hangers

Application conditions


Applications



Suspended ceiling




Suspended ceiling
Hanger type: Eyelet
Wire diameter: 4 mm



Suspended ceiling
Hanger type: Nonius

Base materials



Concrete

Load conditions



Static/
quasi static

Environmental conditions



Dry indoor

Approvals and certificates

Approvals and certificates


Authority	Approval/certificate	Date of issue
Deutsches Institut für Bautechnik (DIBt)	ETA-22/0587	24/07/2023
Document Technique d'Application (DTA)	3.1/24-1087_V1	18/09/2024



- Not all information presented in this product data sheet might be subject to approval/certificate content. Please refer to approval/certificate for further information.

Product data

Dimensions



X-SCO/N ALH37

Material specification and material properties

Designation	Element	Material	Standard
X-SCO/N ALH37	Ceiling fastener	S280GD+ Z140-N-A-C	EN 10346

Designation	Element	Material	Coating	Minimum coating thickness t_c [μm]	Hardness [HRC]
X-SCO/N ALH37	Nail	Carbon steel	Zinc	5	58

Element	Material	Diameter [mm]
Plastic washer	Propylene	8

Application requirements

Base material properties and fastener positioning in base material

	Base material	Concrete
	Concrete class	C20/25 – C40/50
	Base material thickness h_{min} [mm]	80
	Edge distance $c_{1,min}, c_{2,min}$ [mm]	150
	Spacing $s_{1,min}, s_{2,min}$ [mm]	200


Performance data

Single point loads

Designation	Hanger type	Characteristic resistance under tension load	Recommended tension load
		N_{Rk} [kN]	N_{rec} [kN]
X-SCO/N ALH37	Eyelet, Nonius	0.34	0.15

System loads

Maximum allowable ceiling weight [kN/m²]




**Hanger spacing
b [mm]**

	500	600	700	800	900	1000	1100	1200	
Carrying channel/ spacing a [mm]	500	0.60	0.50	0.42	0.37	0.33	0.30	0.27	0.25
	600	0.50	0.41	0.35	0.31	0.27	0.25	0.22	0.20
	700	0.42	0.35	0.30	0.26	0.23	0.21	0.19	0.17
	800	0.37	0.31	0.26	0.23	0.20	0.18	0.17	0.15
	900	0.33	0.27	0.23	0.20	0.18	0.16	0.15	0.13
	1000	0.30	0.25	0.21	0.18	0.16	0.15	0.13	0.12
	1100	0.27	0.22	0.19	0.17	0.15	0.13	0.12	0.11
	1200	0.25	0.20	0.17	0.15	0.13	0.12	0.11	0.10

- Allowable ceiling weights are calculated based on the single point recommended tension load of 0.15 kN.
- The eccentric load introduction into the fastener is already considered in these load values.
- Fastening of redundant non-structural components (details see ETA-22/0587).

Stick rate estimation



Designation	Soft/standard concrete	Tough concrete
X-SCO/N ALH37	> 95 %	90-95 %



- The stick rate indicates the percentage of nails that were driven correctly to carry a load.
- Stick rate can vary from the above values depending on job site conditions.

System recommendation

System recommendation for fastening single nails with powder-actuated tools

Designation	Powder-actuated tool		
	DX 6 F8	DX 5 F8	DX 460 F8
Optional with pole tool	X-6-PT	X-PT 5	X-PT 460
X-SCO/N ALH37	■	■	■

■ = recommended □ = feasible

Cartridge recommendation



Base material	Cartridge color (tool power level)	
	Tool type: DX 6 F8 Cartridge type: 6.8/11 M10 for DX 6	Tool type: DX 5 F8, DX 460 F8 Cartridge type: 6.8/11 M10
Soft/standard concrete	titanium ■ (4-7)	yellow ■, red ■
Tough concrete	titanium ■ (6-8), black ■ (7-8)	red ■, black ■



- Tool power level adjustment by setting tests on site (see chapter quality assurance).
- For more details, please refer to the chapter Accessories and consumables compatibility in the Direct Fastening Technology Manual (DFTM).

Quality assurance

Fastening inspection

Hanger type	Designation	Fastener stand-off h_{NHS} [mm]
 <p>Eyelet</p>	X-SCO/N ALH37	11-15
 <p>Nonius</p>		

- Visible setting failures must be replaced with a new fastener, not in the same hole.
- These are abbreviated instructions which may vary by application. Always review/ follow the instructions accompanying the product.

Fastener program

Item no. and description

Designation	Item no	Description
X-SCO/N ALH37	2375247	Ceiling fastener