



Anchor diameter	[inch]	3/4										
d <sub>bit</sub>	[inch]	3/4										
Anchor Length	[inch]	5 1/2		7			8			10		
h <sub>ef</sub>	[inch]	3 1/4*	3 3/4	3 1/4*	3 3/4	4 3/4	3 1/4*	3 3/4	4 3/4	3 1/4*	3 3/4	4 3/4
min. h <sub>nom</sub>	[inch]	3 13/16	4 5/16	3 13/16	4 5/16	5 5/16	3 13/16	4 5/16	5 5/16	3 13/16	4 5/16	5 5/16
min. h <sub>0</sub> **	[inch]	4	4 1/2	4	4 1/2	5 3/4	4	4 1/2	5 3/4	4	4 1/2	5 3/4
T <sub>inst</sub>	[ft-lb]	110		110			110			110		
T <sub>inst</sub> (Masonry)	[ft-lb]	n/a	70	n/a	70		n/a	70		n/a	70	
d <sub>h</sub>	[inch]	13/16		13/16			13/16			13/16		
WS (Wrench Size)	[inch]	1 1/8		1 1/8			1 1/8			1 1/8		
max. t <sub>fix</sub>	[inch]	15/16	7/16	2 9/16	1 15/16	15/16	3 9/16	2 15/16	1 15/16	5 9/16	4 15/16	3 15/16

Use only carbide-tipped masonry drill bits complying with ANSI B212.15.1994

\* h<sub>ef</sub> not approved for masonry. h<sub>nom</sub> not approved for SS304 or SS316

\*\* For a non-hole cleaning installation (step 1a or 1b), make sure to drill deep enough to achieve h<sub>0</sub>, taking into account the depth of debris remaining in the hole